


R700 Explosion Proof 4-20 mA Transmitter with Display



R700
Remote
Model

R700
Local
Model

The R700 4-20 mA Transmitter is a loop powered transmitter with simultaneous Rate & Total indicator. The R700 features an explosion proof enclosure for hazardous location use. It also features 20 point linearization.

R700-L Local Mount

R700-R Remote Mount

Features and Benefits:

- ✓ Magnetic Pickup Input, Contact Closure Input, DC Pulse Input.
- ✓ 20 point linearization.

R700 – SPECIFICATIONS

Power Supply:	8.5-30 VDC
Accuracy:	0.01% Reading \pm 1 Count
Operating Temperature:	-4° F to +158° F (-20° C to +70° C)
Output:	4-20 mA, Isolated from Ground
Display:	5-digit Rate; 8-digit Totalizer

ENCLOSURE APPROVALS



NEMA
4X



R800 Explosion Proof Totalizer & Rate Indicator



R800
Remote
Model

R800
Local
Model

The R800 is a battery powered Totalizer & Rate Indicator. Both Local and Remote models are available. The R800 features an explosion proof enclosure for hazardous location use. It also features 20 point linearization.

R800-LBAT Local Mount

R800-RBAT Remote Mount

Features and Benefits:

- ✓ Magnetic Pickup Input, Contact Closure Input, DC Pulse Input.
- ✓ 20 point linearization.

R800 – SPECIFICATIONS

Power Supply:	One C Size Lithium Battery Pack
Accuracy:	0.01% Reading \pm 1 Count
Operating Temperature:	-4° F to +158° F (-20° C to +70° C)
Pulse Output:	Isolated Photomos Relay
Display:	5-digit Rate; 8-digit Totalizer

ENCLOSURE APPROVALS



NEMA
4X

